Application No. 10/797,601 Reply to Office Action June 8, 2006

Amendments to the Claims:

The following listing of claims replaces all prior versions, and listings, of claims in the application:

Listing of Claims:

1

- 1. (original) An air filter comprising an essentially metal-free filter insert with a filter medium which forms a hollow cylinder, and end disks arranged on the axial end faces of the filter medium of the filter insert, wherein one end disk forms a closed end of the filter element and has a handle element extending axially away from the filter element, and the other end disk is constructed as a hollow cylinder and comprises a concentric, radially-acting, resilient gasket.
- 2. (original) An air filter according to claim 1, wherein said filter is an air filter for cleaning combustion air for an internal combustion engine.
- 3. (original) An air filter according to claim 1, wherein the filter medium is pleated, and at least the end disk with the handle element is made of a thermoplastic synthetic resin material.
- 4. (original) An air filter according to claim 1, wherein the filter insert further comprises a concentric supporting body adjacent the inside or outside of the cylindrical filter medium.
- 5. (original) An air filter according to claim 1, wherein the hollow cylindrical end disk has a hollow cylindrical, concentric and axially extending collar.
- 6. (original) An air filter according to claim 5, wherein said collar is connected by reinforcing ribs to the end disk.

Application No. 10/797,601 Reply to Office Action June 8, 2006

7. (original) An air filter according to claim 5, wherein the hollow cylindrical collar has an outer circumferential groove in which a gasket having a radially outwardly protruding lip is arranged.

8. (original) An air filter according to claim 1, wherein the filter insert is sealingly connectable via the radial gasket to a connecting profile in the form of a circular ring, the axial end of the collar being bounded axially by a stop through the connecting profile, and a secondary filter element being sealingly connectable to the filter insert via the connecting profile.

9-12. (canceled)